

Adapter

FF-FM/P



Specifications

V2 mrt 27, 2003

| | Port | Range | Min | Typical | Max | Units | Remark | Margin |
|--------------------|---------------|-------|-----|-------------------------------------|------|-------|--------|--------|
| Frequency Range | | | 5 | | 2150 | MHz | | |
| Impedance | | | | 75 | | Ohm | | |
| Equipment Approval | | | | CE | | | | |
| Dimensions | Dimension "a" | | | 30.1 | | mm | | |
| | Dimension "c" | | | 11.6 | | mm | | |
| Material | Material 1 | | | Nickel plated brass | | | | |
| | Material 2 | | | HD PE | | | | |
| | Material 3 | | | Gold plated phosphorus bronze | | | | |
| | Material 4 | | | HD PE | | | | |
| | Material 5 | | | Teflon | | | | |
| | Material 6 | | | Nickel plated brass | | | | |
| | Material 7 | | | Nickel plated SWPA | | | | |
| Temperature Range | | | -10 | | 60 | °C | | |

Ordering Information

| | | | |
|---------|---------|-----------------|----------|
| FF-FM/P | Adapter | Article number: | 10430373 |
|---------|---------|-----------------|----------|

Specifications

V2 mrt 27, 2003

| | Port | Range | Min | Typical | Max | Units | Remark | Margin |
|----------------|-----------|----------------------|-----|---------|-----|-------|--------|--------|
| Insertion Loss | In -> Out | 5 MHz < F < 2150 MHz | | | | 1 | | |
| Return Loss | In/Out | | 20 | | | | | |