


Up to 16 SC adapters subscriber termination solutions

LB-TBA/TBB series

Technetix offers LB-TBA and LB-TBB compact termination closures. These indoor/outdoor, plastic, wall mount termination closures are designed to transition from outdoor incoming fiber to indoor fiber drops. They are ideal for multiple-dwelling unit (MDU) applications for FTTH.

The LB-TBA is capable of handling up to 8 SC adapters, while the LB-TBB handles up to 16 SC adapters.

Both the LB-TBA and LB-TBB are equipped with a hinged adapter tray to allow for fiber splicing, storage and optical splitter installation. Each closure is UV-resistant and weatherproof, with a rubber gasket along the interior edge and at the drop entry ports.




FEATURES

- Compact size (LB-TBA): 8.2"H x 7.1"W x 1.8"D (20.7H x 18.1W x 4.5D cm)
- Compact size (LB-TBB): 11.8"H x 8.7"W x 3.2"D (30.0H x 22.0W x 8.0D cm)
- 2 inlet ports, 8 or 16 output ports; 8-16 outlets for SC adapter
- Can hold mini module PLC splitters. Refer to Technetix' LBPM mini series PLC splitters
- Splice area with fiber storage and management under hinged adapter tray
- IP66 rating for ingress protection (dust and water)
- Ultraviolet (UV)-resistant
- Wall mount and pole mount applications

SPECIFICATIONS

Parameter	Specification	
Capacity (Max.)	12 cores	
Environmental & Physical		
Cable Input Ports	2 Ports	0.5" (12.0 mm) max. diameter
Cable Output Port Capacity	LB-TBA	8 ports
	LB-TBB	16 ports with 0.12" (3.0 mm) max. diameter
OTB Resin	Tensile Strength	≥ 450 kg/cm ² @ 0.4" (10.0 mm)/min.
	Impact Strength	35 kg-cm/cm ² (normal temperature), 10 kg-cm/cm ² (-30 °C/-22 °F)
	Flexural Strength	≥ 450 kg/cm ² @ 0.4" (10.0 mm)/min.
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)	
Dimensions (H x W x D)	LB-TBA	8.2"H x 7.1"W x 1.8"D (20.7H x 18.1W x 4.5D cm)
	LB-TBB	11.8"H x 8.7"W x 3.2"D (30.0H x 22.0W x 8.0D cm)
Weight	2.9 lb (1.3 kg)	



Up to 16 SC adapters subscriber termination solutions

LB-TBA/TBB series



ORDERING INFORMATION (LB-TBA)

Part #	Description
LB-TBA-08-SA-08-SA-1 ⁽¹⁾	8 fiber termination box with 8 SC/APC adapters & 8 SC/APC 1 m (3.3') pigtails. For other adapter types, please contact factory

NOTE:

(1) The LB-TBA comes pre-configured from the factory

ORDERING INFORMATION (LB-TBB)

LB-TBB	-	# of Adapters	-	Adapter Type	-	# of Pigtails	-	Pigtail Type	-	Length of Pigtail
		xx		SA		xx		SA		1
		04 = 4 Adapters		SA = SC/APC		04 = 4 Pigtails		SA = SC/APC		1 = 1 m (3.3')
		08 = 8 Adapters				08 = 8 Pigtails				
		12 = 12 Adapters				12 = 12 Pigtails				
		16 = 16 Adapters				16 = 16 Pigtails				

EXAMPLE:

Part # LB-TBB-16-SA-16-SA-1

16 fiber termination box with 16 SC/APC adapters & 16 SC/APC 1 m (3.3') pigtails. For other adapter types, please contact factory